



DM-750

8 Ω stereo power :	700w
4 Ω stereo power :	990w
8 Ω Bridged power :	1980w
Voltage gain:	35 dB
Damping factor:	300:1
Slew rate:	> 20V/ μ s
Input CMRR(@ 1kHz) :	> 60dB
Frequency response:	20 Hz - 20kHz
Hum and noise:	> 100dB
Input sensitivity:	0.775V(1.0V, 1.4V) for rated power
Input impedance:	> 20K Ω , balanced > 10K Ω , unbalanced
Crosstalk:	> 60dB
THD+N:	< 0.5% 20 Hz - 20kHz
Connectors(per channel):	Input (XLR balanced , RAC unbalanced) Output (binding post, speakon)
Power supply:	220V-230V/50Hz-60Hz
Cooling:	Two(2) variable speed DC fans
Controls:	Mode Selection switch, input sensitivity switch
Indicators(per channel):	Protect led, clip led, signal led, power led.
Protection:	Temperature, DC, sub/ultra-sonic, short Circuit, IGM, output
Dimensions (mm):	88 hx 482w x 320d
Packaged (mm):	135 hx 575w x 438d
Net Weight:	14.2kg
Gross Weight:	16.4kg

E: chris.scott@inspired-audio.co.uk

or visit the website

W: www.inspired-audio.co.uk

Revision: 1 - (30/12/2019)